

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : LMM-6000 METAL MARKING PASTE Product code : LMM-6000.

1.2. Relevant identified uses of the substance or mixture and uses advised against Ceramic covering that will undergo heat treatment on glass and ceramics.

1.3. Details of the supplier of the safety data sheet

Registered company name : GRAVOTECH MARKING SAS. Address : 56, avenue Jean Jaurès.10600.La Chapelle Saint Luc.France. Telephone : +33 (0)3 25 41 65 65. Fax : +33 (0)3 25 79 04 25. e-mail : info@gravograph.fr http://www.gravograph.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable solid, Category 2 (Flam. Sol. 2, H228).

Acute oral toxicity, Category 4 (Acute Tox. 4, H302).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Carcinogenicity, Category 2 (Carc. 2, H351).

Specific target organ toxicity (single exposure), Category 1 (STOT SE 1, H370).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word : DANGER	
Product identifiers :	
042-001-00-9	MOLYBDENUM TRIOXIDE
603-001-00-X	METHANOL
Hazard statements :	
H228	Flammable solid.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer .
H370	Causes damage to organs (if inhaled, if swallowed, in contact with skin).
Precautionary statements - Pr	revention :

SAFETY DATA SHEET (REC LMM-6000 METAL MARKING	GULATION (EC) n° 1907/2006 - REACH) G PASTE - LMM-6000	Version 7.1 (07-08-2018) - Page 2/9
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and	d understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and smoking.	other ignition sources. No
P264	Wash hands thoroughly after handling.	
P280	Wear protective gloves/protective clothing/eye protection/face	e protection.
Precautionary statement	ts - Response :	
P301 + P312	IF SWALLOWED: Call a POISON CENTER/doctor/if you feel	unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortab	ble for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. present and easy to do. Continue rinsing.	Remove contact lenses, if
P308 + P311	IF exposed or concerned: Call a POISON CENTER/doctor/	
P330	Rinse mouth.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	
Precautionary statement	ts - Disposal :	
P501	Dispose of contents/container at a disposal facility in accorda	nce with local regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. N

2. Mixtures			
omposition :			
Identification	(EC) 1272/2008	Note	%
INDEX: 042-001-00-9	GHS08, GHS07	[1]	25 <= x % < 30
CAS: 1313-27-5	Wng	[2]	
EC: 215-204-7	Carc. 2, H351		
	Eye Irrit. 2, H319		
MOLYBDENUM TRIOXIDE	STOT SE 3, H335		
INDEX: 603-002-00-5	GHS02	[1]	25 <= x % < 30
CAS: 64-17-5	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43			
ETHANOL			
CAS: 12001-26-2		[1]	10 <= x % < 15
MICA			
CAS: 14808-60-7		[1]	10 <= x % < 15
EC: 238-878-4			
QUARTZ (SIO2)			
INDEX: 603-001-00-X	GHS02, GHS06, GHS08	[1]	10 <= x % < 10
CAS: 67-56-1	Dgr		
EC: 200-659-6	Flam. Liq. 2, H225		
REACH: 01-2119433307-44	Acute Tox. 3, H331		
	Acute Tox. 3, H311		
METHANOL	Acute Tox. 3, H301		
	STOT SE 1, H370		
(Full text of H-phrases: see section 1	6)		
formation on ingredients :	-		

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

- Do not breathe in smoke.
- In the event of a fire, the following may be formed :
- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) LMM-6000 METAL MARKING PASTE - LMM-6000

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

No data available.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	opm : VLE-mg/m3 : V		Notes :	
67-56-1	260	200 -		-	Peau	
- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :						
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
64-17-5		1000 ppm		A3		
12001-26-2	3 (R) mg/m3					
14808-60-7	0.05 mg/m3	-	-	-	R	
67-56-1	200 ppm	250 ppm		Skin; BEI		

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

	L MARKING PASTE	N (EC) n° 1907/2006 - LMM-6000	- REACH)		version	7.1 (07-08-2018) - Pag
CAS	VME :	VME :	Excess	Notes		
64-17-5		500 ppm 960 mg/m³		2(II)		
67-56-1		200 ppm 270 mg/m ³		4(II)		
- Belgium (Ai	rrêté du 09/03/2014,	-				
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
1313-27-5	0,5 mg/m3					
64-17-5	1000 ppm 1907 mg/m ³					
12001-26-2	3 mg/m ³					
14808-60-7	0,1 mg/m ³					
67-56-1	200 ppm	250 ppm		D		
	266 mg/m ³	333 mg/m ³				
- France (INF	RS - ED984 :2016) :					
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1313-27-5	-	-	-	5	-	-
64-17-5	1000	1900	5000	9500	-	84
14808-60-7	-	0.1 A	-	-	-	25
67-56-1	200	260	1000	1300	(12)	84
- Switzerland	(SUVAPRO 2017) :					
CAS	VME	VLE	Valeur plafond	Notations		
1313-27-5	5 i mg/m³					
64-17-5	500 ppm 960 mg/m ³	1000 ppm 1920 mg/m³		SSC		
12001-26-2	3 a mg/m ³					
14808-60-7	0,15 a mg/m ³			P C1 SSC		
67-56-1	200 ppm 260 mg/m ³	800 ppm 1040 mg/m³		R B SSC		
- UK / WEL (Ū	e limits, EH40/2005, 2	011):			
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
1313-27-5	5 mg/m3	10 mg/m3				
64-17-5	1000 ppm 1920 mg/m ³	- ppm - mg/m ³				
12001-26-2	- ppm 0,8 mg/m ³	- ppm - mg/m³				
14808-60-7	0.3 mg/m3	-	-	-	R	
	200 ppm	250 ppm		Sk		

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

Prescription glasses are not considered as protection.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) LMM-6000 METAL MARKING PASTE - LMM-6000

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Suitable type of protective clothing :

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact. Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Likewise provide safety breathing apparatus for certain short tasks of an exceptional nature or for emergency interventions

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- A3 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Paste.
Colour:	White.
Odour:	Characteristic.

Important health, safety and environmental information

pH :	Not relevant.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
Vapour density :	> 1 (Air=1)
Density :	11.7
Water solubility :	Soluble.
Evaporation rate :	< 1 (BuAC=1)
% VOC :	50

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

- Keep away from :
- strong oxidising agents
- 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Harmful if swallowed.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

Suspected human carcinogen.

Causes damage to organs.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

No toxicological data available for the mixture.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans. CAS 14808-60-7 : IARC Group 1 : The agent is carcinogenic to humans. CAS 1313-27-5 : IARC Group 2B : The agent is possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK) :

WGK 1 (VwVwS vom 27/07/2005, KBws) : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

3175

14.2. UN proper shipping name

UN3175=SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C

(ethanol, methanol)

14.3. Transport hazard class(es)

- Classification :



4.1

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	4.1	F1	II	4.1	40	1 kg	216 274	E2	2	E
							601			
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	4.1	-	П	1 kg	F-A,S-I	216 274	E2			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	4.1	-	11	445	15 kg	448	50 kg	A46	E2	
	4.1	-	П	Y441	5 kg	-	-	A46	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG. For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2017/776 (ATP 10)

- Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 1 (VwVwS vom 27/07/2005, KBws) : Slightly hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) : NFPA 704, Labelling: Health=2 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



- Swiss ordinance on the incentive tax on volatile organic compounds :

 64-17-5
 éthanol, seulement s'il s'agit d'alcools impropres à la consommation (art. 31 de la loi fédérale sur l'alcool)

 67-56-1
 méthanol (alcool méthylique)

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H370	Causes damage to organs .

Abbreviations :

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.